

## ROCKETPORT® EXPRESS Quadcable DB9

Part Number: 30126-4

ROCKETPORT

### KEY FEATURES AND BENEFITS

- x1, x2, x4, x8, x12 or x16 lane PCIe connectivity
- Low-profile or standard-height compatible
- RS-232/422/485 software-selectable ports
- Communications speeds up to 921 Kbps
- RoHS 2 compliant under CE



### PRODUCT DESCRIPTION

Flexible, reliable and high-speed serial port expansion.

The RocketPort EXPRESS Quad DB9 is a four port serial adapter that is compatible with systems that have x1, x2, x4, x8, x12 or x16 PCI Express expansion slots. The card is designed for standard and low-profile PCs and servers and ships with a low-profile and a standard-height bracket.

The product provides support for software-selectable RS-232/422/485 serial communications and data transmission speeds up to 921 Kbps. Serial connections are made utilizing an external quadcable with four DB9M connectors that is included with the product. RocketPort EXPRESS products are European RoHS 2 directive compliant.



## ROCKETPORT SPECIFICATIONS

### HARDWARE

Maximum Cards/System

4

Bus Interface

PCIe

Product Weight (w/ cable)

10.3 oz

Form Factor

Low-profile PCIe or Standard PCIe

### ELECTRICAL SPECIFICATIONS

Current Consumption

3.3VDC or 12VDC

Power Consumption

3.1 W

Surge Protection

15KV @200A for 1ns

### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature

0 to 60°C

Storage Temperature

20 to 85°C

Operating Humidity

NonCondensing

5% to 95%

Altitude

0 to 10,000 Ft

Heat Output

10.6 BTU/Hr

Mean time between failures

48.7 Years

### DEVICE DRIVERS

FreeBSD® 5

FreeBSD® 6

QNX® 6.X

SCO OpenServer™ 5

SCO OpenServer™ 6

Linux

Microsoft® Windows® 7

Microsoft® Windows® 2008 Server

Microsoft® Windows® Vista

Microsoft® Windows Server® 2003

Microsoft® Windows® XP

Microsoft® Windows NT® 4.0 (Legacy)

Microsoft® Windows® 2000 (Legacy)

### SERIAL COMMUNICATIONS

Port Communication

(4) DB9M

Software Interfaces

RS-232/422/485

Baud Rates

300 to 921.6 Kbps

Data Bits

5, 6, 7, or 8

Parity

Odd, Even, None, Mark and Space

Stop Bits

1, 1.5, or 2

### REGULATORY APPROVAL MARKS



### REGULATORY STANDARDS

Immunity

European Standard EN55024

IEC 1000-4-2/EN61000-4-2: ESD

IEC 1000-4-3/EN61000-4-3: RF

IEC 1000-4-4/EN61000-4-4: Fast Transient

IEC 1000-4-5/EN61000-4-5: Surge

IEC 1000-4-6/EN61000-4-6: Conducted

Disturbance

IEC 1000-4-8/EN61000-4-8: Magnetic Field

IEC 1000-4-11/EN61000-4-11: Dip and Voltage

Emission

Canadian EMC Requirements ICES-003

European Standard EN55022

FCC Part 15 Subpart B: Class B limit

AS/NZS CISPR 22

Safety

IEC 60950/EN60950

CSA C22.2 No. 60950/UL60950, Third Edition

European Standard: RoHS 2 compliant under CE

### FEATURES


RoHS 2 compliant under CE

Low-Profile or Standard Height

Easy Setup

5 Year Warranty

### SERIAL PINOUTS

DB9 Male Connector Signals				
				
Pin	RS-232	RS-422	RS-485 (Full-Duplex)	RS-485 (Half-Duplex)
1	DCD	Not used	Not used	Not used
2	RxD	RxD-	RxD-	Not used
3	TxD	TxD-	TxD-	TRxD-
4	DTR	Not used	Not used	Not used
5	Gnd	Not used†	Not used†	Not used†
6	DSR	Not used	Not used	Not used
7	RTS	TxD+	TxD+	TRxD+
8	CTS	RxD+	RxD+	Not used
9	RI	Not used	Not Used	Not Used

† Pin 5 is tied to ground on the board, but is not used in the cable.



#### Warranty Information

Control offers a 30-day satisfaction guarantee and 5-year limited warranty.

#### Sales Support

+1.763.957.6000  
sales@comtrol.com

#### Technical Support

+1.763.957.6000  
www.comtrol.com/  
support

#### Email, FTP, and Web Support

info@comtrol.com  
ftp.comtrol.com  
www.comtrol.com