

Technical Data

Protocol	Hardware and Software Flow Control Data bits: 5, 6, 7 or 8 Parity: Odd, Even, None, Mark and Space Stop Bits: 1, 1.5 or 2 Receive Buffer: 512 Bytes Transmit Buffer: 512 Bytes
Supported baud rates	300 to 460 Kbps
Directive conformity	
Electromagnetic compatibility	
Directive 2014/30/EU	EN 61000-4-2:2009 EN 61000-4-3:2006+A1:2008+A2:2010 EN 61000-4-4:2012 EN 61000-4-5:2014+A1:2017 EN 61000-4-6:2014 EN 61000-4-11:2004+A1:2017
Radio and telecommunication terminal equipment	
Directive 2014/53/EU	
RoHS	EN IEC 63000:2018
Standard conformity	
Electrical safety	CSA C22.2 No. 60950 / UL60950
Emitted interference	EN 55032, FCC Part 15 Subpart B, ICES-003, AS/NZS CISPR 32
Noise immunity	EN 55035:2017-07
Ambient conditions	
Ambient temperature	0 ... 60 °C (32 ... 140 °F)
Storage temperature	-20 ... 85 °C (-4 ... 185 °F)
Relative humidity	max. 95 % non-condensing
Altitude	0 ... 3048 m
Mechanical specifications	
Mass	249.5 g
Construction type	Low-profile PCIe or Standard PCIe
Mounting	Low-profile and standard-height bracket for mounting in PCs and servers
Note	Maximum of 4 PC cards can be used per system

Release date: 2025-01-11 Date of issue: 2025-01-11 Filename: 70116487_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com