

PCIe multiport serial card

RocketPort® EXPRESS

ICRPC-4RJ45-EC

- RS-232/422/485 software selectable interfaces
- Device drivers (Windows and Linux)
- Communications speeds 300 bps to 921 Kbps
- x1, x2, x4, x8, x12 or x16 lane PCIe connectivity
- Low-latency communication supporting the widest variety of applications


PCIe 4-port serial card with RJ45 connectors



Function

Flexible, reliable and high-speed serial port expansion. The RocketPort EXPRESS family comprises serial adapter cards compatible with systems supporting x1, x2, x4, x8, x12 or x16 PCI Express expansion slots. Cards are designed for standard and low-profile PCs and servers and ship with a low-profile and a standard-height bracket. All models feature software-selectable RS-232/422/485 serial communication at data transmission speeds up to 921 Kbps. Connection to serial devices are made utilizing RJ45, DB9 or DB25 fan-out cables or DB9 or DB25 interface boxes, depending on the selected model.

Dimensions



Technical Data

General specifications	
UL File Number	E185802
Functional safety related parameters	
MTBF	118.7 a
Electrical specifications	
Power consumption	1.1 W
Nominal voltage	3.3 V DC or 12 V DC
Surge protection	15 KV / 200 A for 1 ns
Interface	
Interface type	Software selectable interfaces: RS-232 , RS-422 , RS-485
Physical	4

Release date: 2024-10-03 Date of issue: 2024-10-03 Filename: 70116488_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Protocol	Hardware and Software Flow Control Data bits: 5, 6, 7 or 8 Parity: Odd, Even, None, Mark and Space Stop Bits: 1, 1.5 or 2 Receive Buffer: 512 Bytes Transmit Buffer: 512 Bytes
Supported baud rates	300 to 921,6 Kbps
Directive conformity	
Electromagnetic compatibility	
Directive 2014/30/EU	EN 61000-4-2:2009 EN 61000-4-3:2006+A1:2008+A2:2010 EN 61000-4-4:2012 EN 61000-4-5:2014+A1:2017 EN 61000-4-6:2014 EN 61000-4-11:2004+A1:2017
RoHS	EN IEC 63000:2018
Standard conformity	
Electrical safety	CSA C22.2 No. 60950 / UL60950
Emitted interference	EN 55032, FCC Part 15 Subpart B, ICES-003, AS/NZS CISPR 32
Noise immunity	EN 55035:2017-07
Ambient conditions	
Ambient temperature	0 ... 60 °C (32 ... 140 °F)
Storage temperature	-20 ... 85 °C (-4 ... 185 °F)
Relative humidity	max. 95 % non-condensing
Altitude	0 ... 3048 m
Mechanical specifications	
Mass	725 g
Construction type	Low-profile PCIe or Standard PCIe
Mounting	Low-profile and standard-height bracket for mounting in PCs and servers
Note	Maximum of 4 PC cards can be used per system

Release date: 2024-10-03 Date of issue: 2024-10-03 Filename: 70116488_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

