

IO-Link Master DR-8-EIPÄ

Part Number: 99590-6



KEY FEATURES AND BENEFITS

- Eight port IO-Link Master to EtherNet/IP™ with additional digital inputs on every port allowing for a possible 10 DI ports with the two dedicated DI/DO ports
- Screw terminal connectors for IO-Link, Power, and Digital IO
- IP20 DIN rail mount enclosure
- Wide operating temperature (-40° to +70°C)
- LEDs for device, network, and port status
- EtherNet/IP™ and Modbus TCP access to IO-Link process, event, and service data
- EtherNet/IP™ Class 1 (Implicit) and Class 3 (Explicit) interfaces
- Powerful web GUI for configuration and diagnostics, including: IO-Link device management using the IO-Link device manufacturers IODD file for easy device configuration, Automatic data storage (upload and download), Manual data storage (upload and download), Device validation, and Data validation.
- Works with PortVision DX
- IO-Link V1.0 and V1.1 compatibility
- IO-Link COM1, COM2 and COM3 support (230K baud rate)
- Write-to-Tag/File, Read-from-Tag/File
- PLC access to IO-Link ISDU blocks without complex programming
- MultiLink™ – Simultaneously provides IO-Link device access to multiple controllers
- Quality of Services Agreement
- Accredited IO-Link Test Center



PRODUCT DESCRIPTION

Control's IO-Link Master DR-8-EIP combines the benefits of the IO-Link standard with the popular industrial EtherNet/IP protocol by providing a gateway that's a streamlined bridge between the field level sensor network and the industrial EtherNet/IP backbone, making retrofitting or expansion simple.

The IO-Link Master easily installs on a standard DIN rail and incorporates two Fast Ethernet ports, eight IO-Link ports, two DI/DO ports and two DI ports. This product is designed with industrial grade components and redundant power inputs to make it exceptionally reliable for critical applications. The IO-Link Master is easily integrated into a system network, and is compatible with existing and new industrial Ethernet environments.

IO-LINK MASTER SPECIFICATIONS

HARDWARE

Network Interfaces	10/100BASE-TX
Enclosure	Polyamide
Ingress Protection Rating	IP20
Installation and Grounding Method	DIN rail
Network Protocols	EtherNet/IP™, Modbus/TCP (slave)
Connectors	DI/DO, Ethernet, IO-Link, Power
LED Indicators	Ethernet Port Status
Power, Module Status, Network Status, IO-Link, DI, DIO states, and Ethernet Port Status	
Dimensions (L x W x H)	3.9" x 4.5" x 1.8"
	100 x 115 x 45 mm
Product Weight	10 oz
	285 g

IO-LINK INTERFACE SPECIFICATIONS

Connector Type	Screw Terminal
Number of Ports	8
IO-Link Version	Supports V1.0 and V1.1
Configurations per port	IO-Link, or DI or DO on Pin 4 DI (dedicated) on Pin 2
IO-Link Mode Transfer Rates	4.8K (COM1) 38.4K (COM2) 230.4K (COM3)
Baud Rate Recognition	Automatic
Output Current on IO-Link Connectors (Ports 1-8)	C/Q on Pin 4 200mA (Maximum)
Overload Protection	Yes - Vs on Pins 1, 3 and C/Q on Pin 4
Short Circuit Protection	Yes - C/Q on Pin 4
Cable Length (Max.)	20m

DIGITAL INPUTS C/Q (SIO Mode Using IO-Link Ports)

Sensor Current Load (Maximum)	200mA
Input Characteristics	IEC 61131-2 Type 1 and Type 3 Compliant
Short-Circuit and Overload protection	Yes
Short-Circuit proof	Yes
Input Current Limitation	Yes
C/Q Input Threshold	Low: 8.0 - 11.5V High: 10.5 - 13.0V
Cable Length (Max.)	30m

DIGITAL OUTPUTS C/Q (SIO Mode Using IO-Link Ports)

Actuator Current Load (Maximum)	200mA
Input Characteristics	IEC 61131-2 Type 1 and Type 3 Compliant
Short-Circuit and Overload protection	Yes
Short-Circuit proof	Yes
Input Current Limitations	Yes
Output Function	PNP/NPN
Cable Length (Max.)	30m

DIGITAL INPUTS C/Q (DI and DIO Pin)

Sensor Current Load (Maximum)	200mA
Input Characteristics	IEC 61131-2 Type 1 and Type 3 Compliant
Short-Circuit and Overload protection	Yes
Short-Circuit proof	Yes
Input Current Limitation	Yes
C/Q Input Threshold	Low: 5.2 - 6.4V High: 6.8 - 8.0V
Cable Length (Max.)	30m

DIGITAL OUTPUTS DIO PIN

Actuator Current Load (Maximum)	200mA
Short-Circuit and Overload protection	Yes
Short-Circuit proof	Yes
Input Current Limitations	Yes
Output Function	PNP/NPN
Cable Length (Max.)	30m

DEDICATED DIGITAL IO PORTS (Digital Input Mode)

Connector Type	Screw Terminal
Number of Ports	2 (D1 & D3)
Cable Length (Max.)	30m

DIGITAL INPUTS/OUTPUTS

Connector Type	Screw Terminal
Number of Ports	2 (D2 & D4)
Configurations per port	DI/DO (configurable) = 1 DI (dedicated) = 1
Cable Length (Max.)	30m

DIGITAL OUTPUTS

Actuator (Sensor) Current Load (Max.)	200mA
Lamp Load (Max.)	4W
Over Load and Short Circuit Protection	Yes
Switching Output	PNP, NPN

ETHERNET INTERFACE SPECIFICATIONS

Connector Type	RJ45
Number of Ports	2
Ethernet Specification	10/100BASE-TX
Standards	IEEE802.3: 10BASE-T IEEE 802.3u: 100BASE-TX
Auto-MD/MDI-X	Yes
Auto-Negotiation	Yes
Link Distance	100m
Cable Types	Unshielded or Shielded twisted pair
IPv4 Addressing	Yes

ETHERNET/IP INTERFACE SPECIFICATIONS

Supported PLCs	Including but not limited to: Control Logix Compact Logix RSLogix SLC 500 PLC5 MicroLogix
Other Class 1 or Class 3 EtherNet/IP may be supported	
ISDU Read & Writes	Up to 40 individual commands in one EtherNet/IP message
ISDU Commands	Selectable byte swapping (none, 16-bit, or 32-bit) Selectable payload sizes (4 to 232 bytes) ISDU block index ISDU sub-index Length of read or write Data payload
Web Page Configuration	Provides the following capabilities: Port configuration for ISDU Data, Process Data, Transfer Mode, Read/Write, Write PDI to Tag/File, and Read PDO from Tag/File. EtherNet/IP configuration: Time to Live (TTL) Network Value Multicast IP Address Allocation Control User-Defined Number of Multicast IP Addresses User-Defined Multicast Starting IP Address Session Encapsulation Timeout
Diagnostics	Yes
Electronic Data Sheets (EDS)	Yes
Sample PLC Programs	Yes

MODBUS TCP INTERFACE

Supported Controllers (Modbus TCP Masters)	PLC HMI SCADA OPC Server
Supported Clients	Any Modbus TCP Client Applications on phones/tables
Web Page Configuration	Port configuration for ISDU Response Timeout, Process Data, and Transfer Mode
Diagnostics	Yes

DR-8-EIP FEATURES

Data Storage	Automatic or Manual - Upload and/or Download
Device Validation	Yes
Data Validation	Yes
Powerful Web Interface	Provides the following capabilities: Firmware upgradable Password protected with Admin, Operator, and User accounts ISDU batch handling Load IODD files to configure the IO-Link device IODD Handler parses xml files making them readable and configurable Log files Upgradable Firmware

Yes (Web page or using PortVision DX)	Yes
Remote Parameterization	Yes
Mobile App Support	Simplify monitoring of control system Process and Service Data using simple standard clients available for free in Google Play and Apple App Store

ELECTRICAL SPECIFICATIONS

DC Input Voltage Range	18-30VDC
Current Consumption (Max.)	4.3A @ 24VDC
Current Consumption (w/out devices)	100mA
Current Consumption (with load)	4.04A
Power Consumption (w/out load)	2.4W
Power Connectors	Screw terminal

ENVIRONMENTAL SPECIFICATIONS

Air Temperature	System On System Off	-40°C to +70°C -40°C to +70°C
Operating Humidity (non-condensing)		10% to 95%
Storage Humidity (non-condensing)		10% to 95%
Shock/Vibrations	EN60068-2-6 EN60068-2-27	

EXPORT INFORMATION

Package Weight	1.1 lbs 481.94 g
Package Dimensions	9.2" x 7.25" x 2.5" 233 x 184 x 64 mm
UPC Code	7-56727-99590-6
Country of Origin	USA
ECCN	5A992
Schedule B Number	8517.62.0050

REGULATORY APPROVALS

Immunity	European Standard 61000-6-2 International Standard IEC 61000-6-2 IEC 61131-2 IEC 1000-4-2/EN 61000-4-2: Electrostatic Discharge (ESD) IEC 1000-4-3/EN 61000-4-3: Radiated, Radio-Frequency (RF) IEC 1000-4-4/EN 61000-4-4: Fast Transient/Burst IEC 1000-4-5/EN 61000-4-5: Surge IEC 1000-4-6/EN 61000-4-6: Conducted disturbance IEC 1000-4-8/EN 61000-4-8: Magnetic Field IEC 1000-4-11/EN 61000-4-11: Dips and Voltage Variations
Emissions	European Standard EN 61000-6-4 International Standard IEC 61000-6-4 AS/NZS CISPR-11 FCC Part 15 Subpart B: Class A limit Canadian EMC requirements ICES-001
Safety	CSA C22.2 No. 61010-1-12 / CSA C22.2 No. 61010-1-201 UL 61010-1/UL 61010-1-201
Other	Ingress Protection rating IP@ (IEC 60529) Environmental & Mechanical testing per IEC/EN 61131-2 European Standard: 2011/65/EU (RoHS2) Directive.
Regulatory Approval Symbols	



Warranty Information

Control offers a 30-day satisfaction guarantee and 5-year limited warranty.

Sales Support

+1.763.957.6000
sales@comtrol.com

Technical Support

+1.763.957.6000
www.comtrol.com/support

Email, FTP, and Web Support

info@comtrol.com
ftp.comtrol.com
www.comtrol.com