

# SFP Fiber Transceiver Series



## Spotlight

- All SFPs have been tested with the best operating performance on EtherWAN switches
- The characteristics are performed in accordance with Telcordia Specification GR-468-CORE
- Single +3.3V Power Supply
- RoHS Compliant and Lead-free
- AC/AC Differential Electrical Interface
- Eye Safety Designed to meet Laser Class 1 compliant with EN 60825-1
- Compliant with Multi-Source Agreement (MSA) Small Form Factor Pluggable (SFP)
- EMC requirement meets FCC in the United States and CENELEC EN 55022 (CISPR 22) in Europe

## Ordering Information

### 100BASE SFP Series\*

#### Non-Hardened (Operating Temperature: 0 to 70°C/32 to 158°F)

Model Name	Distance	Cable Type	Connector Type	Wavelength	Link Budget**	Optical Output Power	Sensitivity
EXFE-R1S4-05H1	100m	-	TX	-	-	-	-
EX-0155NSP-MB2L	2Km	62.5/125µm, MM	Duplex LC	1310nm	13dBm	-19 to -14dBm	-32dBm
EX-LM38-A3S-TC-N-B3	2Km	62.5/125µm/50/125µm, MM	Single LC	TX: 1310nm/RX: 1550nm	18dBm	-10 to 0dBm	-28dBm
EX-LM48-A3S-TC-N-B5	2Km	62.5/125µm/50/125µm, MM	Single LC	TX: 1550nm/RX: 1310nm	18dBm	-10 to 0dBm	-28dBm
EX-0155TSP-MB5L	15Km	9/125µm, SM	Duplex LC	1310nm	19dBm	-15 to -8dBm	-34dBm
EX-0155TBP-MB5L	20Km	9/125µm, SM	Single LC	TX: 1310nm/RX: 1550nm	18dBm	-14 to -8dBm	-32dBm
EX-0155TBP-LB5L	20Km	9/125µm, SM	Single LC	TX: 1550nm/RX: 1310nm	18dBm	-14 to -8dBm	-32dBm
EX-0155TSP-MB6L	40Km	9/125µm, SM	Duplex LC	1310nm	30dBm	-5 to 0dBm	-35dBm

## 100BASE SFP Series\*

Hardened (Operating Temperature: -40 to 85°C/-40 to 185°F)

Model Name	Distance	Cable Type	Connector Type	Wavelength	Link Budget**	Optical Output Power	Sensitivity
EX-0155NSP-MB2L-A	2Km	62.5/125µm, MM	Duplex LC	1310nm	13dBm	-19 to -14dBm	-32dBm
EX-LM38-A3S-TI-N-B3	2Km	62.5/25µm/50/125µm, MM	Single LC	TX: 1310nm/RX: 1550nm	18dBm	-10 to 0dBm	-28dBm
EX-LM48-A3S-TI-N-B5	2Km	62.5/125µm/50/125µm, MM	Single LC	TX: 1550nm/RX: 1310nm	18dBm	-10 to 0dBm	-28dBm
EX-0155TSP-MB5L-A	15Km	9/125µm, SM	Duplex LC	1310nm	19dBm	-15 to -8dBm	-34dBm
EX-0155TBP-MB5L-A	20Km	9/125µm, SM	Single LC	TX: 1310nm/RX: 1550nm	18dBm	-14 to -8dBm	-32dBm
EX-0155TBP-LB5L-A	20Km	9/125µm, SM	Single LC	TX: 1550nm/RX: 1310nm	18dBm	-14 to -8dBm	-32dBm
EX-0155TSP-MB6L-A	40Km	9/125µm, SM	Duplex LC	1310nm	29dBm	-5 to 0dBm	-34dBm
EX-0155TBP-MB6L-A	40Km	9/125µm, SM	Single LC	TX: 1310nm/RX: 1550nm	26dBm	-8 to -3dBm	-34dBm
EX-0155TBP-KB6L-A	40Km	9/125µm, SM	Single LC	TX: 1550nm/RX: 1310nm	26dBm	-8 to -3dBm	-34dBm

\* More SFP options upon the request.

\*\* Link Budget data is based on pair of the same SFP modules.

## Gigabit SFP Series\*

Non-Hardened (Operating Temperature: 0 to 70°C/32 to 158°F)

Model Name	Distance	Cable Type	Connector Type	Wavelength	Link Budget**	Optical Output Power	Sensitivity
EX-1250NSP-SB1L S	275m/550m	62.5/125µm/50/125µm, MM	Duplex LC	850nm	7.5dBm	-9.5 to -4dBm	-17dBm
EX-1250TBP-MB1L S	550m	62.5/125µm/50/125µm, MM	Single LC	TX: 1310nm/RX: 1550nm	7dBm	-10 to -4dBm	-17dBm
EX-1250TBP-LB1L S	550m	62.5/125µm/50/125µm, MM	Single LC	TX: 1550nm/RX: 1310nm	7dBm	-10 to -4dBm	-17dBm
EX-1250TSP-MB2L S	2Km	62.5/125µm, MM	Duplex LC	1310nm	13.5dBm	-9.5 to -3dBm	-23dBm
EX-1250TSP-MB4L S	10Km	9/125µm, SM	Duplex LC	1310nm	11.5dBm	-9.5 to -3dBm	-21dBm
EX-1250TBP-MB4L S	10Km	9/125µm, SM	Single LC	TX: 1310nm/RX: 1550nm	12dBm	-9 to -3dBm	-21dBm
EX-1250TBP-KB4L S	10Km	9/125µm, SM	Single LC	TX: 1550nm/RX: 1310nm	12dBm	-9 to -3dBm	-21dBm
EX-1250TSP-MB5L S	20Km	9/125µm, SM	Duplex LC	1310nm	15dBm	-9 to -3dBm	-24dBm
EX-1250TBP-MB5L S	20Km	9/125µm, SM	Single LC	TX: 1310nm/RX: 1550nm	15dBm	-8 to -3dBm	-23dBm
EX-1250TBP-KB5L S	20Km	9/125µm, SM	Single LC	TX: 1550nm/RX: 1310nm	15dBm	-8 to -3dBm	-23dBm
EX-LS38-C3L-TC-N-EB (DDM)	40Km	9/125µm, SM	Duplex LC	1310nm	20dBm	-3 to +2dBm	-23dBm
EX-LS38-C3L-TC-N-CE (DDM)	40Km	9/125µm, SM	Single LC	TX: 1310nm/RX: 1550nm	20dBm	-3 to +2dBm	-23dBm
EX-LS48-C3L-TC-N-CE (DDM)	40Km	9/125µm, SM	Single LC	TX: 1550nm/RX: 1310nm	20dBm	-3 to +2dBm	-23dBm
EX-LS38-C3U-TC-N-CE (DDM)	60Km	9/125µm, SM	Single LC	TX: 1310nm/RX: 1550nm	24dBm	0 to +5dBm	-24dBm
EX-LS48-C3U-TC-N-CE (DDM)	60Km	9/125µm, SM	Single LC	TX: 1550nm/RX: 1310nm	23dBm	-2 to +4dBm	-25dBm
EX-LS48-C3U-TC-N-EB (DDM)	70Km	9/125µm, SM	Duplex LC	1550nm	23dBm	0 to +5dBm	-23dBm
EX-LS48-C3U-TC-N51-CE (1510nm) (DDM)	80Km	9/125µm, SM	Single LC	TX: 1510nm/RX: 1570nm	24dBm	-2 to +3dBm	-26dBm
EX-LS48-C3U-TC-N57-CE (1570nm) (DDM)	80Km	9/125µm, SM	Single LC	TX: 1570nm/RX: 1510nm	24dBm	-2 to +3dBm	-26dBm
SFPGIS90C (DDM)	90Km	9/125µm, SM	Duplex LC	1550nm	27dBm	0 to +5dBm	-27dBm

## Gigabit SFP Series\*

Hardened (Operating Temperature: -40 to 85°C/-40 to 185°F)

Model Name	Distance	Cable Type	Connector Type	Wavelength	Link Budget**	Optical Output Power	Sensitivity
EXGT-R154-05H3	100m	TX	TX	-	-	-	-
EX-1250NSP-SB1L-A S	275m/550m	62.5/125µm/50/125µm, MM	Duplex LC	850nm	7.5dBm	-9.5 to -4dBm	-17dBm
EX-1250TBP-MB1L-A S	550m	62.5/125µm/50/125µm, MM	Single LC	TX: 1310nm/ RX: 1550nm	7dBm	-10 to -4dBm	-17dBm
EX-1250TBP-LB1L-A S	550m	62.5/125µm/50/125µm, MM	Single LC	TX: 1550nm/ RX: 1310nm	7dBm	-10 to -4dBm	-17dBm
EX-LM38-C3S-TI-N-CE (DDM)	550m	62.5/125µm, MM	Single LC	TX: 1310nm/ RX: 1550nm	8dBm	-10 to +2dBm	-18dBm
EX-LM48-C3S-TI-N-CE (DDM)	550m	62.5/125µm, MM	Single LC	TX: 1550nm/ RX: 1310nm	10dBm	-8 to 0dBm	-18dBm
EX-1250TSP-MB2L-A S	2Km	62.5/125µm, MM	Duplex LC	1310nm	13.5dBm	-9.5 to -3dBm	-23dBm
EX-1250TSP-MB4L-A S	10Km	9/125µm, SM	Duplex LC	1310nm	11.5dBm	-9.5 to -3dBm	-21dBm
EX-1250TBP-MB4L-A S	10Km	9/125µm, SM	Single LC	TX: 1310nm/ RX: 1550nm	12dBm	-9 to -3dBm	-21dBm
EX-1250TBP-KB4L-A S	10Km	9/125µm, SM	Single LC	TX: 1550nm/ RX: 1310nm	12dBm	-9 to -3dBm	-21dBm
EX-1250TSP-MB5L-A S	20Km	9/125µm, SM	Duplex LC	1310nm	15dBm	-9 to -3dBm	-24dBm
EX-1250TBP-MB5L-A S	20Km	9/125µm, SM	Single LC	TX: 1310nm/ RX: 1550nm	15dBm	-8 to -3dBm	-23dBm
EX-1250TBP-KB5L-A S	20Km	9/125µm, SM	Single LC	TX: 1550nm/ RX: 1310nm	15dBm	-8 to -3dBm	-23dBm
SFPGYS20M (DDM)	20Km	9/125µm, SM	Single LC	TX: 1310nm/ RX: 1550nm	15dBm	-8 to -2dBm	-23dBm
SFPGZS20M (DDM)	20Km	9/125µm, SM	Single LC	TX: 1550nm/ RX: 1310nm	15dBm	-8 to -2dBm	-23dBm
EX-LS38-C3L-TI-N-CE (DDM)	40Km	9/125µm, SM	Single LC	TX: 1310nm/ RX: 1550nm	20dBm	-3 to +2dBm	-23dBm
EX-LS48-C3L-TI-N-CE (DDM)	40Km	9/125µm, SM	Single LC	TX: 1550nm/ RX: 1310nm	20dBm	-3 to +2dBm	-23dBm
EX-LS38-C3U-TI-N-CE (DDM)	60Km	9/125µm, SM	Single LC	TX: 1310nm/ RX: 1550nm	24dBm	0 to +5dBm	-24dBm
EX-LS48-C3U-TI-N-CE (DDM)	60Km	9/125µm, SM	Single LC	TX: 1550nm/ RX: 1310nm	23dBm	-2 to +4dBm	-25dBm
EX-LS38-C3L-TI-N-EB (DDM)	40Km	9/125µm, SM	Duplex LC	1310nm	20dBm	-3 to +2dBm	-23dBm
EX-LS48-C3U-TI-N-EB (DDM)	70Km	9/125µm, SM	Duplex LC	1550nm	23dBm	0 to +5dBm	-23dBm

\* More SFP options upon the request.

\*\* Link Budget data is based on pair of the same SFP modules.

## 10GBASE SFP Series\*

Non-Hardened (Operating Temperature: 0 to 70°C/32 to 158°F)

Model Name	Distance	Cable Type	Connector Type	Wavelength	Link Budget**	Optical Output Power	Sensitivity
SFPTIM3AE (DDM)	300m	62.5/125µm/50/125µm, MM	Duplex LC	850nm	2.8dBm	-7.1 to -1dBm	-9.9dBm
SFPTIS10E (DDM)	10Km	9/125µm	Duplex LC	1310nm	8.4dBm	-6 to +0.5dBm	-14.4dBm

## 10GBASE SFP Series\*

Hardened (Operating Temperature: -40 to 85°C/-40 to 185°F)

Model Name	Distance	Cable Type	Connector Type	Wavelength	Link Budget**	Optical Output Power	Sensitivity
SFPTIM3AM (DDM)	300m	62.5/125µm/50/125µm, MM	Duplex LC	850nm	2.8dBm	-7 to -1dBm	-9.9dBm
SFPTIS10M (DDM)	10Km	9/125µm	Duplex LC	1310nm	6.4dBm	-8 to +0.5dBm	-14.4dBm
SFPTIS20M (DDM)	20Km	9/125µm	Duplex LC	1310nm	9.4dBm	-5 to +1dBm	-14.4dBm

\* More SFP options upon the request.

\*\* Link Budget data is based on pair of the same SFP modules.